Product information

Top Tec 4100 SAE 5W-40

LIQUI MOLY

Description

Fully synthetic low SAPS motor oil that provides exceptional protection against wear, reduced oil consumption and improved fuel consumption. Suitable for alternative fueled CNG and LPG vehicles. Use with extended oil change intervals as per manufacturer.

Properties

- outstanding engine cleanliness
- smooth engine running
- ideal with turbochargers and catalytic converters
- high shear stability
- high lubrication reliability
- long engine service life
- miscible with all commercially available motor oils
- optimum oil pressure under all operating conditions
- instant lubrication after cold start

Specifications / Approvals

ACEA C3 • API SN • MB-Approval 229.31 • Porsche A40 • VW 505 00 • VW 505 01

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required

BMW Longlife-04 (up to 2018) • Fiat 9.55535-H2 • Fiat 9.55535-M2 • Fiat 9.55535-S2 • Ford WSS-M2C 917-A • GM dexos2 • Renault RN 0700 • Renault RN 0710

Technical data

SAE class (engine oils) 5W-40

SAE J300

Density at 59 °F 0,855 g/cm³

DIN 51757

Viscosity at 104 °F 88 mm²/s

ASTM D 7042-04

Viscosity at 212°F 14,3 mm²/s

ASTM D 7042-04

Viscosity at -31 °F (MRV) < 60000 mPas

ASTM D4684

Viscosity at -22 °F (CCS) \leq 6600 mPas

ASTM D5293

Viscosity index 169

DIN ISO 2909

HTHS at 302 °F ≥ 3.5 mPas.

ASTM D5481

Pour point -43 °F

DIN ISO 3016

Evaporation loss (Noack) 9,5 %

CEC-L-40-A-93

Technical data

Flash point 449 °F

DIN ISO 2592

Total base number 7,5 mg KOH/g

PI 55/05/17/2024

DIN ISO 3771

Sulfate ash $\leq 0.8 \text{ g/}100 \text{ g}$

DIN 51575

Color number (ASTM) L 2,5

DIN ISO 2049

Areas of application

For gasoline or diesel engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers.

Application

Observe the manufacturers instructions!

Available pack sizes

1 l Canister plastic 2329

USA-AND-CANADA-EN-F

5 l Canister plastic 2330

USA-AND-CANADA-EN-F

60 l Black plate barrel 22067

USA-AND-CANADA-EN-F

205 l Black plate barrel 22068

USA-AND-CANADA-EN-F

Our information is based on thorough research and may be considered reliable, although not legally binding.

Phone: +49 (0)731/1420-0 Fax: +49 (0)731/1420-82 e-mail: info@liqui-moly.de