

Top Tec ATF 1200

Description

Fully synthetic automatic transmission fluid with modern additive technology provides high thermal stability, excellent wear protection and correct friction behavior. Excellent low temperature behavior. Compatible with most common seal materials.



Properties

- highest thermal stability
- excellent corrosion protection
- enables a multifaceted range of applications
- excellent viscosity/temperature properties
- very good low-temperature properties
- high chemical resistance
- excellent wear protection
- optimum stability to aging
- outstanding friction characteristics

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required

Allison C4 • Allison TES 295 • BMW 7045 E • BMW 8072 B • BMW LA 2634 • BMW LT 71141 • Caterpillar TO-2 • Chrysler ATF +3 • Chrysler ATF +4 • Daimler NAG-1 • Dexron III H • Ford Mercon V • Honda ATF Z1 (except CVT) • Hyundai SP-II • Hyundai SP-III • JASO 1-A • JWS 3309 (Aisin Warner) • Kia SP-II • Kia SP-III • MAN 339 Typ V1 • MAN 339 Typ Z1 • MAN 339 Typ Z2 • Mazda ATF M-III • Mazda ATF M-V • MB 236.2 • MB 236.5 • MB 236.6 • MB 236.7 • MB 236.9 • MB 236.10 • MB 236.11 • MB 236.91 • Mitsubishi SP-II • Mitsubishi SP-III • Nissan AT-Matic D Fluid • Nissan AT-Matic J Fluid • Nissan AT-Matic K Fluid • Subaru ATF • Toyota Type T-II • Toyota Type T-IV • Voith H55.6335.XX (G 607) • Volvo 97340 • Volvo 97341 • VW G 052 162 • VW G 052 990 • VW G 055 025 • ZF TE-ML 02F • ZF TE-ML 03D • ZF TE-ML 04D • ZF TE-ML 05L • ZF TE-ML 09 • ZF TE-ML 11A • ZF TE-ML 11B • ZF TE-ML 14A • ZF TE-ML 14B • ZF TE-ML 17C

Technical data

Density at 59 °F	0,850 g/cm ³ DIN 51757
Viscosity at 104 °F	36,4 mm ² /s ASTM D 7042-04
Viscosity at 212°F	6,9 mm ² /s ASTM D 7042-04
Viscosity at -40 °F (Brookfield)	<= 20000 ASTM D 2983-09
Viscosity index	150 DIN ISO 2909
Pour point	-54 °F DIN ISO 3016

Technical data

Flash point	446 °F DIN ISO 2592
Color / appearance	rot

Areas of application

For automatic transmissions, manual transmissions, power steering systems and hydraulics in automotive and commercial vehicles where a ATF fluid meeting current specifications is required or recommended.

Comment

⚠ WARNING: Cancer- www.P65Warnings.ca.gov

Application

Observe the manufacturers instructions! Optimum efficiency and product performance are only possible when the product is used undiluted.

Available pack sizes

1 l Can plastic	20018 USA-AND-CANADA-EN-F
5 l Canister plastic	20020 USA-AND-CANADA-EN-F
20 l Canister plastic	20022 USA-AND-CANADA-EN-F

Our information is based on thorough research and may be considered reliable, although not legally binding.